



Product Data Sheet



Release Agent

FEATURES:

- Long Term Biodegradable
- Non-toxic
- Non-carcinogenic
- Non-evaporative
- Protects against corrosion
- Protects against end-grain swelling
- Good resistance to mineral acids
- Greater Coverage

PACK SIZES:

- 2.9 Litre Jerry Can
- 5 Litre Jerry Can
- 20 Litre Drum

USES:

- Formwork release agent (Mix @ 6:1)
- Protection of doors, windows, railings etc. from concrete and paint overspray
- Lubricant for jacks and fittings (Mix @ 4:1)
- Protects end grains from swelling on timber formwork
- Extends the life of timber formwork
- Corrosion protection of metal moulds

CONTENTS:

Lanolin, blended with non-regulated, non-ozone depleting paraffin carrier's to enable ease of application and enhance penetration.

PHYSICAL PROPERTIES:

- Appearance: Light brown liquid with distinctive wool fleece and solvent odour.
- Boiling Point: Approx. 110-200°C
- Flash Point: > 82°C
- Specific Gravity: 0.81 - 0.83 @ 24°C
- Solubility in Water: Emulsifiable

CONTACT DETAILS FOR FURTHER INFORMATION:

Lanotec Australia Pty Ltd
Phone: 07 3373 3700
Email: info@lanotec.com.au

Fax: 07 3373 3777
Web: www.lanotec.com.au

NATURALLY BETTER